

HYBRIDIZATION INCUBATOR

Combi-SV12



- Well designed air mixing system provides accurate temperature control.
- Digital temperature control.
- Rubber magnet seal door.
- Powerful and quiet DC motor.
- Designed to accommodate optional rocking platform in its interior.
- Movable sensor: Thermo sensing probe can be closely placed to samples on rocking platform.
- Rocker(CR-95) can be operated inside the incubator with the electrical socket provided after removing rotor.
- Both function for rocking and shaking in one chamber.

SPECIFICATION

MODEL		Combi - SV12
Temperature range		Ambient + 5 deg.C ~80 deg.C
Temperature accuracy		±0.1 deg.C
Rotation speed		Variable 0~40 rpm
Shaking speed		Variable 0~300 rpm
Timer		3hrs with hold/dial
Dimension (mm)	out side	W468×D435×H443(W18.4"×D17"×H17.4")
	in side	W365×D280×H286(W14.4"×D11"×H11.3")
Weight		36kgs(79.2 Lbs)
Power		AC 110V (AC 220V)

labkorea

ROTORS

MODEL	BOTTLE SIZE	CAPACITY	IMAGE
RT-4	80mm diameter bottle	4ea	
RT-6	60mm diameter bottle	6ea	
RT-10	40mm diameter bottle	10ea	
RT-8V	50mm conical Tube	8ea	
RT-24H	50mm conical Tube	24ea	
RT200-64	1.5ml Eppendorf Tube	64ea	
RT200-96	1.5ml Eppendorf Tube	96ea	
RT200-128	1.5ml Eppendorf Tube	128ea	

labkorea

BOTTLES



For precise tests, A disk filter could be attached into the hole as the follow images




MODEL	SIZE	COMENT
BT40-120	40mm diameter X 120mm length	with silicon cap
BT40-200	40mm diameter X 200mm length	with silicon cap
BT60-200	60mm diameter X 200mm length	with silicon cap
BT80-200	80mm diameter X 200mm length	with silicon cap

CR95



Able to use the CR95 (compact Roker) in all the ovens using inside power supplier.

RK-H



(Rocking Platform)

Simply set it up for all the ovens



labkorea